



MANUFACTURING SPECIFICATIONS FOR 48 SWD STOCK SHEETS

MATERIAL: STAINLESS STEEL

PROFILE: STANDARD

STYLE	WT/SF LBS	DESIGN		OPENINGS		STRAND		OVERALL THICKNESS	OPEN AREA
		SWD	LWD	SWO	LWO	WIDTH	THICKNESS		
1/4" 18	0.92	0.312	1.000	0.191	0.616	0.072	0.048	0.150	54%
1/2" 18	0.61	0.480	1.200	0.382	0.913	0.073	0.048	0.150	69%
1/2" 16	0.76	0.480	1.200	0.362	0.965	0.073	0.060	0.150	69%
1/2" 13	1.45	0.480	1.200	0.306	0.817	0.093	0.090	0.200	60%
3/4" 18	0.45	0.923	2.000	0.760	1.650	0.105	0.048	0.212	81%
3/4" 16	0.52	0.923	2.000	0.816	1.632	0.105	0.060	0.200	80%
3/4" 13	0.85	0.923	2.000	0.784	1.494	0.105	0.090	0.200	80%
3/4" 9	1.70	0.923	2.000	0.703	1.484	0.140	0.135	0.290	69%
1-1/2" 16	0.38	1.330	3.000	1.269	2.461	0.101	0.060	0.210	85%
1-1/2" 13	0.57	1.330	3.000	1.228	2.517	0.101	0.090	0.210	85%
1-1/2" 9	1.28	1.330	3.000	1.105	2.366	0.151	0.135	0.310	79%
TOLERANCES	+/- 10%	NOMINAL	NOMINAL	NOMINAL	NOMINAL	+/- 10%	+/- 10%	NOMINAL	NOMINAL



MANUFACTURING SPECIFICATIONS FOR 48 SWD STOCK SHEETS

MATERIAL: STAINLESS STEEL

PROFILE: FLAT

STYLE	WT/SF LBS	DESIGN		OPENINGS		STRAND		OVERALL THICKNESS	OPEN AREA
		SWD	LWD	SWO	LWO	WIDTH	THICKNESS		
1/4" 18	0.86	0.312	1.020	0.146	0.666	0.079	0.041	0.041	66%
1/2" 18	0.57	0.480	1.260	0.315	0.955	0.083	0.041	0.041	66%
1/2" 16	0.72	0.480	1.260	0.295	1.000	0.083	0.051	0.051	66%
1/2" 13	1.38	0.480	1.260	0.269	0.854	0.105	0.076	0.076	56%
3/4" 18	0.44	0.923	2.100	0.750	1.813	0.118	0.041	0.041	75%
3/4" 16	0.50	0.923	2.100	0.700	1.729	0.103	0.051	0.051	79%
3/4" 13	0.82	0.923	2.100	0.667	1.653	0.101	0.076	0.076	79%
3/4" 9	1.63	0.923	2.100	0.606	1.622	0.158	0.115	0.115	66%
1-1/2" 16	0.36	1.330	3.200	1.058	2.610	0.114	0.051	0.051	84%
1-1/2" 13	0.55	1.330	3.200	1.085	2.613	0.114	0.076	0.076	79%
1-1/2" 9	1.21	1.330	3.200	0.977	2.594	0.158	0.115	0.115	76%
TOLERANCES	+/- 10%	NOMINAL	NOMINAL	NOMINAL	NOMINAL	+/- 10%	+/- 10%	NOMINAL	NOMINAL